

Typ	Nennweite	Förderhöhe H max.	Baulänge
PrimAX 15-3 130 RED	DN 15	3 m	130 mm
PrimAX 15-4 130 RED	DN 15	4 m	130 mm
PrimAX 15-6 130 RED	DN 15	6 m	130 mm
PrimAX 15-8 130 RED	DN 15	7.5 m	130 mm
PrimAX 25-3 130 RED	DN 25	3 m	130 mm
PrimAX 25-3 180 RED	DN 25	3 m	180 mm
PrimAX 25-4 130 RED	DN 25	4 m	130 mm
PrimAX 25-4 180 RED	DN 25	4 m	180 mm
PrimAX 25-6 130 RED	DN 25	6 m	130 mm
PrimAX 25-6 180 RED	DN 25	6 m	180 mm
PrimAX 25-8 130 RED	DN 25	7.5 m	130 mm
PrimAX 25-8 180 RED	DN 25	7.5 m	180 mm
PrimAX 32-3 170 RED	DN 32	3 m	170 mm
PrimAX 32-3 180 RED	DN 32	3 m	180 mm
PrimAX 32-4 170 RED	DN 32	4 m	170 mm
PrimAX 32-4 180 RED	DN 32	4 m	180 mm
PrimAX 32-6 170 RED	DN 32	6 m	170 mm
PrimAX 32-6 180 RED	DN 32	6 m	180 mm
PrimAX 32-8 170 RED	DN 32	7.5 m	170 mm
PrimAX 32-8 180 RED	DN 32	7.5 m	180 mm